

MUSICAL FIDELITY



MX-VYNL – PHONO STAGE

SPECIFICATION

Output

4 Volts RMS single ended from RCA sockets
8 Volts RMS balanced from XLR sockets

Performance

Frequency response: RIAA ± 0.1 dB IEC ± 0.1 dB

MM

Channel separation: < -86 dB
SNR A-wtd: < -101 dB
THD: $< 0.007\%$
XLR input: 5mV / 2.5mV selectable
70mV max (23dB headroom)

MC

Channel separation: < -83 dB
SNR A-wtd: < -98 dB
THD: $< 0.01\%$
XLR input: 0.8mV / 0.4mV selectable, 12mV max
(24dB headroom)

Inputs

Balanced Mini-XLR
RCA 1 pair RCA sockets

Outputs

Balanced XLR male sockets EIA Standard RS-297-A
RCA 1 pair RCA sockets

Power

Connector: 1.3mm pin DC power jack
Outboard power supply: 12V/500mA DC
Mains voltages 100-240VAC 50-60Hz universal
worldwide supply
Consumption < 8 watts

Weight

Unpacked / packed:
1.9 kg (4.25lbs) / 2.4 kg (5.25 lbs)

Dimensions

Width 220 mm (8.66")
Height (including feet) 53mm (2")
Depth (front to back) 215mm (8.5")

Included accessories

Mains adaptor
Manual